



## 3mm Silicon PIN Photodiode

MODEL NO : PD204-6B

---

### ■ Features :

- Fast response time
- High photo sensitivity
- Small junction capacitance

### ■ Description :

PD204-6B is a high speed and high sensitive PIN photodiode in a standard 3Φ plastic package. The device is spectrally matched to infrared emitting diode.

### ■ Applications :

- High speed photo detector
- Camera
- Optoelectronic switch
- VCRs ,Video camera
- Floppy disk drive

PART NO.	CHIP	LENS COLOR
	MATERIAL	
PD	Silicon	Black

---





## 3mm Silicon PIN Photodiode

MODEL NO : PD204-6B

### ■ Absolute Maximum Ratings at $T_A = 25^\circ\text{C}$

Parameter	Symbol	Rating	Unit	Notice
Reverse Voltage	$V_R$	32	V	
Power Dissipation	$P_d$	150	mW	
Lead Soldering Temperature	$T_{sol}$	260	$^\circ\text{C}$	4mm from mold body less than 5 seconds
Operating Temperature	$T_{opr}$	-25 ~ +85	$^\circ\text{C}$	
Storage Temperature	$T_{stg}$	-40 ~ +85	$^\circ\text{C}$	

### ■ Electronic Optical Characteristics :

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Rang of Spectral Bandwidth	$\lambda_{0.5}$	----	840-1200	----	nm	-----
Wavelength of Peak Sensitivity	$\lambda_P$	----	980	----	nm	-----
Open-Circuit Voltage	$V_{oc}$	----	0.42	----	V	$E_e=5\text{m W/c m}^2$ $\lambda_p=940\text{nm}$
Short-Circuit Current	$I_{sc}$	----	15	----	$\mu\text{A}$	
Reverse Light Current	$I_L$	----	15	----	$\mu\text{A}$	$E_e=5\text{m W/c m}^2$ $\lambda_p=940\text{nm}$ $V_R=5\text{V}$
Dark Current	$I_d$	----	----	10	nA	$E_e=0\text{m W/c m}^2$ $V_R=10\text{V}$
Reverse Breakdown Voltage	$BV_R$	32	170	----	V	$E_e=0\text{m W/c m}^2$ $I_R=100\mu\text{A}$
Total Capacitance	$C_t$	----	5	----	pF	$E_e=0\text{m W/c m}^2$ $V_R=5\text{V}, f=1\text{MHz}$
Rise/Fall Time	$t_r/t_f$	----	6/6	----	nS	$V_R=10\text{V}$ $R_L=1\text{K}\Omega$



**3mm Silicon PIN Photodiode**

MODEL NO : PD204-6B

**Typical Electrical/Optical/Characteristics Curves**

Fig. 1 Power Dissipation vs. Ambient Temperature




Fig. 2 Spectral Sensitivity




Fig.3 Dark Current vs. Ambient Temperature




Fig.4 Reverse Light Current vs.  $E_e$




Fig.5 Terminal Capacitance vs. Reverse Voltage





Fig.6 Response Time vs. Load Resistance





# EVERLIGHT ELECTRONICS CO., LTD.

DEVICE NUMBER : DPD-020-040      REV : 1.1  
 ECN : \_\_\_\_\_      PAGE : 5/7

## 3mm Silicon PIN Photodiode



MODEL NO : PD204-6B

### ■ Reliability Test Item And Condition

The reliability of products shall be satisfied with items listed below.

Confidence level:90%

LTPD:10%

NO.	Item	Test Conditions	Test Hours/ Cycle	Sample Size	Failure Judgement Criteria	Ac/Re
1	Solder Heat	TEMP : 260°C ± 5 °C	5 sec	22 PCs	$I_L \leq L_x \times 0.8$  L :Lower specification limit	0/1
2	Temperature Cycle	H : +85°C    30 min  L : -55°C    30 min	50 cycle	22 PCs		0/1
3	Thermal Shock	H : +100°C    5 min  L : -10°C    5 min	50 cycle	22 PCs		0/1
4	High Temperature Storage	TEMP. : +100°C	1000 hrs	22 PCs		0/1
5	Low Temperature Storage	TEMP. : -55°C	1000 hrs	22 PCs		0/1
6	DC Operating Life	$V_R=5V$	1000 hrs	22 PCs		0/1
7	High Temperature / High Humidity	85°C / 85% R.H.	1000 hrs	22 PCs		0/1


## 3mm Silicon PIN Photodiode

MODEL NO : PD204-6B

### ■ Test Method For Reverse Light Current

Condition:  $E_e=5\text{mW}/\text{cm}^2, V_R=5\text{V}$ 

Test Item: Reverse Light Current

Unit :  $\mu\text{A}$ 




DEVICE NUMBER : DPD-020-040      REV : 1.1  
ECN : \_\_\_\_\_      PAGE : 7/7

## 3mm Silicon PIN Photodiode

MODEL NO : PD204-6B

### ■ Packing Specifications



### ■ Packing Quantity Specification

1. 1000 Pcs/1Bag , 4 Bags/1Box
2. 10 Boxes/1Carton